

FIG. 1A





FIG. 1B


2/12



Light intensity guided through a bent optical fiber with and without sol-gel silica coating

FIG.2


3/12



Experimental set-up for testing the optical fiber moisture sensor

FIG.3


4/12



Light intensity guided through a sol-gel silica coated bent fiber probe in air gas of different humidity

FIG.4


5/12



dB response of a sol-gel silica coated bent fiber probe to air gas of different humidity against wavelength

FIG.5


6/12



Calibration curve of a sol-gel silica coated bent fiber probe for moisture sensing

FIG.6


7/12



Time response of a sol-gel silica coated bent fiber probe to moisture change

FIG.7


8/12



Comparison of response time of a sol-gel silica coated bent fiber moisture sensor with a capacitance based commercial sensor

FIG.8


9/12



Calibration curves of a sol-gel silica coated bent fiber sensor on different dates
(The probe was soaked in water in between each test)

FIG.9


10/12



Long-term soil moisture monitoring using a sol-gel silica coated bent fiber sensor
(The coated bent fiber probe was buried in soil sample without any package protection)

FIG.10


11/12



Laboratory set-up for testing the sensor of this invention for monitoring moisture inside a concrete block

FIG.11

12/12



Preliminary test result of optical fiber sensor for monitoring moisture in concrete block

FIG.12